### f-POD

#### **Specification Includes**

7" Colour Touch-Screen Control Panel Simultaneous Multicar Use **ATC Automatic Track Compensation Comprehensive Downloadable History** 30 Litre/min Flow Rate Pump **80kg Capacity Heavy Duty Tank Explosion Proof Pump Motor ATEX Approved Components Internal 12VDC Rechargeable Battery Onboard Intelligent Battery Monitor High 210 Series Quality Hoses Low Friction Anti-Static Wheels Heavy Duty Flight Case Housing Auxiliary Battery Socket** 640w x 680d x 950h mm Weight Empty: 91kg

#### **Options**

Fast Acting Anti-Siphon Control
Dry Break Couplings
Other Capacities
Safety Drum Adaptor



## f-POD \_\_\_\_ ultra

#### f-POD ultra Overall Dimensions

Dimensions:
640w x 680d x 950h mm
Weight Empty:
91kg

TOP VIEW

SIDE VIEW

FRONT VIEW



#### Essential Equipment Consortium Ltd

Unit 4 Maizefield, Hinckley Fields Ind. Est. Hinckley, LE10 1YF. ENGLAND
Tel: 00 44 (0)1455 891623 Fax: 00 44 (0)1455 634587
e: enquiries@eec-ltd.co.uk

WWW-eec-ltd.com

### f-POD \_\_\_\_ultra

#### **Intelligent Race Fuel Bowser**





### f-POD

### **Innovation**

EEC Performance Systems consulted with experienced race engineers to provide software control second to none.

The 7" full colour touch screen PC, combined with our inspired, step by step graphical instructions, means by using the f-POD, refuelling errors are a thing of the past.



Inspired, Step By Step, Graphical Instructions

The f-POD can run multiple drivers simultaneously, recording a data history which is available to view instantly on screen and to download via USB for further analysis.





# f-POD \_\_\_\_\_ultra

#### **Accuracy**

The f-POD ultra employs the highest quality weighing components. This ensures fuel delivery and reception, in and out of your cars fuel cell, within a repeatable accuracy of 0.05kg, which means you can always be confident with your race fuel calculations.

The f-POD ultra employs clever routines to adjust for an empty or full fuel hose, recording precisely actual fuel in and out of your car every time.



Our unique ATC system ensures the f-POD weighs your fuel accurately at any circuit in the world without the need for recalibration!



t: 00 44 (0)1455 891623 e: enquiries@eec-ltd.co.uk www-eec-ltd.com

### f-POD \_\_\_\_ultra

### Safety

The f-POD is constructed with total safety a priority.

All of the electronic components and battery are housed in a sealed steel cabinet to eliminate any possible spark risk. The pump utilises an explosion proof motor and ancillary components are ATEX approved.

The programmable 'Push to Pump' button can be configured for all processes, stopping the pump immediately upon release.

Programmable 'Push to Pump' Button



The f-POD includes an antistatic bonding lead to keep the car and bowser at the same potential

Fuel transfer is by high quality hoses which are included in our price! The heavy duty fuel tank is totally sealed in normal

conditions featuring an Over/Under Pressure Relief Valve with Vapour Capture.

The substantial flight case housing sits on the highest quality, low friction, anti-static wheels.

The f-POD is CE marked and

The f-POD is CE marked and meets all current directives.

